

TX1920 ZOOM



FEATURES

LED chip: TYANSHINE 19X20W RGBW 4 in 1 LED, stable performance, long life span.
use integrated combination optical lens, high brightness, long life span, multi-function.
build-in color calibration system, for make sure every equipment mixed color consistent.
The light have three kinds of work mode: silent, standard, high brightness for different work place. Heat dissipation use intelligent temperature control.

7-55° zoom

Light Source / Power System

Voltage : AC100V-240V~/ 50-60Hz

Power : 403W, PF0.98

LED chip : TYANSHINE 19x20W RGBW 4 in 1 LED

Average life span : 30000h

Optical system : High precision combination structure,
high permeable glass light rod +PMMA lens

Color / GOBO / Effects

Zoom angle : 7°-55°

Color : RGBW macro color system.

Color temperature adjustable range : 2500~10000K

CRI : Ra≥75

Zoom system : Linear electric zoom

Ring Control : Yes Independent control of outer and inner ring

Effect macro : Static effect macro functions and Dynamic effects
macro function

Strobe : 1-30Hz electronic strobe and random strobe

Dimmer : Electronic dimmer, provides four dimming options

Control System

Pan/Tilt : Pan/Tilt Travel: 540°/210°; Pan/Tilt Fine: 2.11°/0.82°;

Pan/Tilt Speed : 2.5S/1.0S

Control Mode : DMX512、 RDM

Channel : Standard-15CH、 Extend-24CH

Display : 2.4 inches LCD12864 display screen. With Chinese and English two version language.

Working mode : Silent mode; Standard mode; High Brightness mode

Intelligent control : Display board can record device's using time , show device's temperature, channel data and software version .

Other functions

Error alarm : Automatic alarming for fixture error

Software upgrade : Upgrade via DMX connector

Magnetic encoder : non-touch magnetic rotation encoder , 100% correct position memory

RDM : RDM signal two-way transmission

Safety Devices : Over current and overheat protection

Appearance Parameters

Outlooking : Metal base and anti-fire plastic

IP rate : IP20

Light size : 338×216×422mm

Box Size : 400×270×495mm

N.W : 10.6kg G.W : 12.6kg

Flycase Size(4pcs in 1) : 920×580×615mm

N.W : 42.4kg G.W : 78.8kg

