

TX1940 ZOOM



The Light Sky TX1940 ZOOM is a high-brightness, compact, and energy-efficient LED zoom moving head light for color rendering or backdrop lighting on stage. Light sky has been providing intelligent lighting solutions for the entertainment and architectural industries; you will find all the information you need to

know about the wash moving head light if you are interested in moving head wash zoom. Please get in touch with us, and our team of experts will get back to you as soon as possible.

FEATURES

- High brightness : 700W
- Color mixing : RGBW macro color system
- Smart cooling system, low noise.
- Tiny volume & light weight
- Equipped with the latest USB upgrading system
- Light Source / Power System
- Voltage : AC100V~240V 50/60Hz
- Power : 632W
- Lumen : 10715 Lm
- Power factor : PF0.985
- LED chip : OSRAM 40W, RGBW 4 in 1 LED chip
- LED QTY : 19PCS
- Lifespan : 30% weaker after 20000h.

Color / GOBO / Effects

- Beam angle : Zoom function min.5°,max.55°.
- Color : RGBW macro color system.
- Strobe : 1-30 times/ second electronic strobe and random strobe.
- Dimmer : 65536 class electronic dimmer

Control System

- Pan/Tilt : 540°/2.5 s, 220°/1.0s
- Control Mode : DMX512, RDM, Stand-alone mode ,Wireless DMX512(optional)
- Channel : Standard(13CH)、Extended(23CH)、Simple Mode(9CH)、HSIC Mode(12CH)
- Focus and Lens : Combination lens with high precision,linear adjustment

Other Functions

- Display Menu : 1、 The display panel adopts a 2.0-inch LCD12864 (LCD screen) in both Chinese and English, which facilitates the operation and browse.
- 2、 Menus can record fixture's using time and show its temperature, channel data and software version .
- 3、 The display menu setting can edit the procedure
- IP set : equipped with long-life battery, IP could be set without power.
- Software upgrade : upgrading software by USB.
- IP rate : IP20
- Fixture Protection : The power would be turned off automatically

for fixture's overheating or failed operation of cooling system.

Cooling : Forced ventilation via axial fans.

Appearance Parameters

- Outlooking : adopt ABS anti-fire plastic.
Light size : 425×300×506 (mm)
Carton Size : 580×500×375(mm)
N.W : 21kg G.W : 25.8kg
Flight case : 880X500X640(mm) (2pcs in 1)
N.W : 42kg G.W : 75kg

